



Holger Heinicke
Rotdornstr. 11
16833 Karweseesee
Germany

Phone.: +49 33922/90209
Fax: +49 33922/90379
Funk: +49 173/1519907
www.heipro.com

TECHNICAL DATA SHEET ATG015SP – VEGETABLE OIL GENERATOR

DESCRIPTION and TECHNICAL DATA

1. STRUCTURE

- Runs with Straight Vegetable Oil (SVO, PPO e.g. rape oil, soya oil, palm oil, sun flower oil,...), Waste Vegetable Oil (WVO) or common Diesel fuel
- Easy to use by means of fully automatic PLC-control, supports local or remote operation
- Suitable as backup system for solar and wind power plants
- SUPERSILENCED (68 dB(A)±3 at 7 mt.)
- Engine/alternator monoblock unit coupled through flexi-disc couplings, installed on a welded steel baseframe, complete with antivibration mountings
- Soundproof canopy that can be opened in two sections, made of 20/10 sheet steel, soundproof material, internal silencer, handles and stay rod, internal fuel tank cap, pull-out lifting hook
- Industrial painting in RAL 1004 (golden yellow)
- Integrated daily-service diesel fuel tank - 70 litres, vegetable oil tank connected external (not included)
- Fuel consumption at 75% of load: approx. 2.8 L/h
- Lead acid batteries: 12 V / 85 Ah
- Dimensions (mm): L= 1750 x W= 750 x H= 1100 - weight (Kilos): 650

2. ELECTRIC START PANEL

- Earth fault device
- Magnetothermal circuit breaker
- Socket 32A 230V, Socket 32A 400V
- Voltmeter + phase selector switch
- Ammeter, Frequency meter, Hours run meter
- Engine safety device: high water temperature, low oil pressure, battery charger fault
- Low fuel level switch
- Emergency stop button





Holger Heinicke
Rotdornstr. 11
16833 Karweese
Germany

Phone.: +49 33922/90209
Fax: +49 33922/90379
Funk: +49 173/1519907
www.heipro.com

3. EQUIPMENT SPECIFICATION (according ISO 8528/1)

- Standby power at cos ϕ 0.8 : 14.5 kVA
- Prime power at cos ϕ 0.8 : 13.3 kVA
- Standby power at cos ϕ 0.8 : 11.6 kW
- Prime power at cos ϕ 0.8 : 10.6 kW
- Frequency : 50 Hz
- Voltage available to the terminals : 400/230 V

4. ENGINE

- 4 stroke motor - water cooled
- Brand and model : PERKINS 403D-15
- Governor : mechanical
- Max power : 18 hp
- R.P.M. : 1500
- Cylinders : 3
- Displacement : 1496 cc
- Emission standard : Stage 2

5. ALTERNATOR

- Synchronous generator with electronic governor and AVR (Automatic Voltage Regulator)
- Brand and model : MECC ALTE ECO3 - 2L/4 (OR SIMILAR BRAND)
- Poles : 4
- Stator/rotator insulation : Class H
- Protection level : IP23
- Continuous power (50 Hz) : 13.5 kVA

Further information on the Internet at:

<http://www.heipro.com/plant-oil-generator.htm>